


Geberit washbasin tap Piave, wall-mounted, mains operation, for concealed function box



Application purposes

- For installation in Geberit elements for washbasins, wall-mounted tap with concealed function box
- For connecting cold and hot water (only for model with mixer or thermostatic mixer)
- For connecting cold or mixed water (only for model without mixer)
- For use with stainless steel bowls
- Model with mixer or thermostatic mixer not suitable for continuous flow heater, see technical data sheet "Washbasin taps with continuous flow heaters"
- For panelling thickness 10–50 mm

Characteristics

- Tap group I in accordance with DIN 4109
- Infrared user detection
- Vandal-resistant
- Temperature presetting via mixer (only for models with mixer or thermostatic mixer)
- Not possible to set just hot water or just cold water (only for model with mixer or thermostatic mixer)
- Thermostat according to EN 1111 (only for model with thermostatic mixer)
- Scald protection by limiting the water temperature to 42 °C (only for models with thermostatic mixer)
- Thermal disinfection according to DVGW W 551 possible
- Functions can be set and queried with the Geberit Service Handy
- With integrated check valve
- Functional unit with built-in basket filters

Technical data

Protection degree	IPX4
Nominal voltage	110-240 V AC
Mains frequency	50-60 Hz
Operating voltage	4.5 V DC
Power consumption	0.1 W
Operating pressure	0.5-10 bar
Recommended operating pressure with thermostatic mixer	0.5-5 bar
Recommended operating pressure with thermostatic mixer	50-500 kPa
Differentiated pressure CW/WW	≤ 1.5 bar
Maximum test pressure, water	16 bar
Maximum test pressure, air / inert gas	3 bar
Ambient temperature	1–40 °C
Storage temperature	-20 – +70 °C
Water temperature, adjustment range with thermostatic mixer	20-42 °C
Maximum operating temperature, water, short-term	90 °C
Flow rate at 3 bar	5 l/min
Interval flush time, factory setting	5 s
Product material	Brass chrome-plated / plastic

Scope of delivery

- Washbasin tap
- IR sensor with connection cable
- Control electronics
- Functional unit
- Power supply unit
- Tap aerator key
- Fastening material

To order additionally

- Geberit element for washbasin
- Cover plate

Art. no.	Colour / surface	Mixer	L	
116.261.21.1	bright chrome-plated	without mixer	17 cm	
116.262.21.1	bright chrome-plated	with mixer	17 cm	
116.281.21.1	bright chrome-plated	without mixer	22 cm	
116.282.21.1	bright chrome-plated	with mixer	22 cm	
116.267.21.1	bright chrome-plated	with thermostatic mixer	17 cm	New
116.287.21.1	bright chrome-plated	with thermostatic mixer	22 cm	New