


Litocare Stone Glossy

STAIN-PROOF IMPREGNATING AGENT WITH SEMI-GLOSS EFFECT FOR MARBLE AND GRANITE, TERRACOTTA AND ABSORBENT MATERIALS



DESCRIPTION

Litocare Stone Glossy is a stain-proof and dirt-proof protective impregnating agent with glossy finish for the treatment of medium-high absorbency surfaces. It creates a warm, wet effect, features excellent dirt-proof and stain-proof properties and offers surfaces a semi-glossy appearance. This treatment facilitates routine maintenance, reducing surface friction and inhibiting the penetration of dirt.

ADVANTAGES

- Suitable for interior and exterior applications.
- Enhances the tone and color of the surfaces on which it is applied
- Resistant to UV rays and weathering
- Gives a semi-gloss finish
- High penetrating capacity

PACKAGING

1 l (0.26US gal lqd) metal bottles (boxes with 12 pcs)

FIELDS OF APPLICATION

The product is recommended for natural stones (marble, granite, cobblestone etc.) with non-glossy finishes, terracotta and materials with a medium-high absorbency rate.

APPLICATION

Shake well before use.
Apply a thin and consistent film of pure product on a dry and clean surface using a brush, roller, airless sprayer or fleece.
After application, wait approximately 5-10 minutes depending on the absorbency of the material, then spread the excess product evenly and leave to dry.
After removing the excess product, wait at least 6 hours before opening the treated area to traffic.
Particularly in the case of more compact surfaces, the product tends to create a semi-glossy film that can be brushed once dry using a white non-abrasive disc pad to enhance shine.

WARNINGS

- It is important to apply the recommended quantities and carefully remove any excess product within the indicated time frames to prevent greasiness. Always perform a spot test first to assess the result
- Spread the product only on perfectly clean and dry surfaces
- Do not use the product on wet or heated surfaces
- Do not wash the surface within the first 24 hours of applying the treatment. Waiting up to 48 hours allows the product to firmly adhere to the substrate for a longer-lasting effect over the years
- In the case of accidental leaks, soak up the product using an absorbent material (paper, sawdust, vermiculite, etc.) and dispose of it in a suitable container
- Do not use the product for applications not stated in this technical sheet
- If in doubt, contact the Litokol S.p.A Technical Help Service.

SAFETY INFORMATION

Consult the product safety data sheet, available on request.
PRODUCT FOR PROFESSIONAL USE

IDENTIFICATION DATA

Appearance	Clear liquid
Color	Colorless
Odor	Organic solvent
Customs code	38249097
Shelf life	24 months in original packaging away from sources of heat and direct sunlight.

APPLICATION DATA

Treatment time	5 - 10 minutes
Flammable	YES
Flash point (ASTM D 56)	+30°C (86°F) open cup
Specific gravity	0.84 kg/l (1.85lb/US gal lqd)
Application	Brush, roller, airless sprayer or fleece
Application temperatures	From +5°C to +35°C (+41°F to +104°F)
Consumption	15 - 20 m ² /l (16.4 - 21.9yd ² /US gal lqd)

NOTES

Data detection at temperature +23 °C (+68°F), R.H. 50% and with no wind. May vary depending on the specific conditions of the installation site.

Scheda **n. 401**
Revisione **n. 1**
Data: **January 2021**

The information and provisions contained in this technical data sheet reflect our best experience. Given the impossibility of directly intervening on the conditions of the work site and execution of the works, they represent indications of a general nature, which are in no way binding on our Company. It is therefore advisable to perform a spot test to check the suitability of the product for the intended use. In any case, users must determine whether or not it is suitable for the intended use and shall assume all associated responsibility.

Litokol S.p.A.
Via G. Falcone 13/1
42048 Rubiera (RE) Italy
Tel. +39 0522 622811
Fax +39 0522 620150
info@litokol.it

www.litokol.it

