Using Geberit washbasin taps with CLAGE E-mini instant water heaters

1 About this document

This Technical Information is about the use of Geberit washbasin taps with CLAGE E-mini instant water heaters.





The document shows which Geberit washbasin taps with electronic flush actuation can be combined with which electronic mini instant water heaters from CLAGE. This information is a joint recommendation from Geberit and CLAGE. The document also contains additional information such as planning rules, connection examples and accessories.

Contents

2	"Suitable CLAGE E-mini instant water heaters", page 2	
3	"Suitable Geberit deck-mounted taps with/without exposed function box", page 3	
4	"Suitable Geberit deck-mounted taps with concealed function box", page 5	
5	"Suitable Geberit wall-mounted taps with concealed function box", page 7	

Contact: Valid from: 01.04.2021

Using Geberit washbasin taps with CLAGE E-mini instant water heaters

2 Suitable CLAGE E-mini instant water heaters

The Geberit washbasin taps referred to below can be combined with the following CLAGE E-mini instant water heaters:

E-mini instant water heater		Tap aerator	Temperature setting
O QUE	MCX3, 3.5 kW, 230 V, with mains plug Art. no. 1500-15003	CSP3 (included in scope of delivery)	35 or 38 °C
SE S	MCX7, 6.5 kW, 400 V, fixed connection Art. no. 1500-15007	CSP6 (included in scope of delivery)	35 or 38 °C

Contact: Valid from: 01.04.2021

Using Geberit washbasin taps with CLAGE E-mini instant water heaters

3 Suitable Geberit deck-mounted taps with/without exposed function box

Washbasin tap		Tap aerator	Run-on time
	Geberit washbasin tap Piave, deckmounted, mains operation, with exposed function box, without mixer Art. no. 116.161.21.1	Geberit tap aerator (accessory): • with MCX3 E-mini instant water heater: 1.9 l/min, art. no. 243.637.00.1 • with MCX7 E-mini instant water heater: 3.8 l/min, art. no. 243.636.00.1	3seconds
	Geberit washbasin tap Brenta, deck-mounted, mains operation, with exposed function box, without mixer Art. no. 116.171.21.1		
	Geberit washbasin tap type 185, mains operation, without mixer Art. no. 116.135.21.1	CLAGE tap aerator (included in scope of delivery with E-mini instant water heater):	0
	Geberit washbasin tap type 186, mains operation, without mixer Art. no. 116.136.21.1	with MCX3 E-mini instant water heater: CSP3 with MCX7 E-mini instant water heater: CSP6	3 seconds

Contact: Valid from: 01.04.2021


Using Geberit washbasin taps with CLAGE E-mini instant water heaters

Planning rules:


- · Only use washbasin taps without mixers.
- Only use the water-saving tap aerators specified in the table.
- Use washbasin taps with mains operation. Washbasin taps with battery operation can also be used, but a mains connection is usually present because of the E-mini instant water heater.
- Use the Geberit Service Handy to set the run-on time to 3 seconds:
 - Geberit washbasin taps Piave and Brenta: menu item 43 = [3]
 - Geberit washbasin taps type 185/186: menu item 30 = [C] and menu item 43 = [3]

3.1 Connection examples

For Geberit washbasin taps type 185/186



For Geberit washbasin taps Piave/Brenta with exposed function box



Contact: Valid from: 01.04.2021

Using Geberit washbasin taps with CLAGE E-mini instant water heaters

4 Suitable Geberit deck-mounted taps with concealed function box

Washbasin tap		Tap aerator	Run-on time
	Geberit washbasin tap Piave, deck-mounted, mains operation, without mixer Art. no. 116.181.21.1	Geberit tap aerator (accessory): • with MCX3 E-mini instant water heater: 1.9 l/min, art.	3 seconds
	Geberit washbasin tap Brenta, deckmounted, mains operation, without mixer Art. no. 116.191.21.1	no. 243.637.00.1 • with MCX7 E-mini instant water heater: 3.8 l/min, art. no. 243.636.00.1	o seconds


Planning rules:

- Only use washbasin taps without mixers.
- Only use the water-saving tap aerators specified in the table.
- Use washbasin taps with mains operation. Washbasin taps with battery operation can also be used, but a mains connection is usually present because of the E-mini instant water heater.
- Use the Geberit Service Handy to set the run-on time to 3 seconds (menu item 43 = [3]).

Contact: Valid from: 01.04.2021


Using Geberit washbasin taps with CLAGE E-mini instant water heaters

4.1 Connection example



Installation notes

- Fasten the elbow tap connector for holding the angle stop valves to the crossbar of the concealed function
- Drill fastening holes for mounting the elbow tap connectors in the crossbar of the concealed function box on site.
- When selecting the elbow tap connector, bear in mind that a distance of 7 cm is required between the crossbar and the front edge of the installation element; see graphic below.



- 1 Angle stop valve
- 2 Tiles
- 3 Tile adhesive
- 4 Panelling
- 5 Installation element
- 6 Elbow tap connector
- 7 Crossbar of concealed function box

Contact: Valid from: 01.04.2021

Using Geberit washbasin taps with CLAGE E-mini instant water heaters

5 Suitable Geberit wall-mounted taps with concealed function box

Washbasin tap		Tap aerator	Run-on time
	Geberit washbasin tap Piave, wall-mounted, mains operation, without mixer Outlet length 17 cm: art. no. 116.261.21.1 Outlet length 22 cm: art. no. 116.281.21.1	Geberit tap aerator (accessory): • with MCX3 E-mini instant water heater: 1.9 l/min, art.	
	Geberit washbasin tap Brenta, wall-mounted, mains operation, without mixer Outlet length 17 cm: art. no. 116.271.21.1 Outlet length 22 cm: art. no. 116.291.21.1	no. 243.637.00.1 with MCX7 E-mini instant water heater: 3.8 l/min, art. no. 243.636.00.1	3seconds


Planning rules:

- Only use washbasin taps without mixers.
- Only use the water-saving tap aerators specified in the table.
- Use washbasin taps with mains operation. Washbasin taps with battery operation can also be used, but a mains connection is usually present because of the E-mini instant water heater.
- Use the Geberit Service Handy to set the run-on time to 3 seconds (menu item 43 = [3]).

Contact: Valid from: 01.04.2021


Using Geberit washbasin taps with CLAGE E-mini instant water heaters

5.1 Connection example



Installation notes

- Fasten the elbow tap connector for holding the angle stop valves to the crossbar of the concealed function box.
- Drill fastening holes for mounting the elbow tap connectors in the crossbar of the concealed function box on site.
- When selecting the elbow tap connector, bear in mind that a distance of 7 cm is required between the crossbar and the front edge of the installation element; see graphic below.



- 1 Angle stop valve
- 2 Tiles
- 3 Tile adhesive
- 4 Panelling
- 5 Installation element
- 6 Elbow tap connector
- 7 Crossbar of concealed function box

Contact: Valid from: 01.04.2021