

DECLARATION OF PERFORMANCE No. 0394

- 1. Unique identification code of the product-type: Fugabella Eco Silicone
- 2. Intended use/es: Sealant for external and internal, non-structural use: facade joints; included cold climates.
- 3. Manufacturer: Kerakoli France 25, avenue de l'Industrie 69960 Corbas France
- 4. System/s of AVCP:

System 3 and System 3 for reaction to fire

5. Harmonised standard: EN 15651-1:2012

Notified body/ies: SKZ - TeConA GmbH, No. 1213

6. Declared performance/s:

EN15651-1 F-EXT-INT-CC (Class 25 LM)

Pretreatment: Method A

Substrate: glass; without primer


aluminium without primer mortar M1 with primer

Essential characteristics		Performance
Reaction to fire		Class E
Resistance to flow		≤3 mm
Loss of volume		≤10 %
Tensile properties at maintained extension after water immersion		Pass
Secant tensile modulus at -30°C		≤0,9 MPa
Tensile properties at maintained extension for non-structural sealants used in joints in cold climate areas (-30°C)		Pass
Durability		Pass
Release of dangerous substances		See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Etienne Guichard (legal representative)

At Corbas, on 30/09/2019



kerakoll.com



DECLARATION OF PERFORMANCE No. 0394

1. Unique identification code of the product-type: Fugabella Eco Silicone

2. Intended use/es: Sealant used for sealing glazing applications; included cold climates.

3. Manufacturer: Kerakoli France 25, avenue de l'Industrie 69960 Corbas - France

4. System/s of AVCP:

System 3 and System 3 for reaction to fire

5. Harmonised standard: EN 15651-2:2012

Notified body/ies: SKZ - TeConA GmbH, No. 1213

6. Declared performance/s:

EN15651-2 G-CC (Class 25LM)

Pretreatment: Method A

Substrate: glass; without primer

aluminium; without primer

Essential characteristics		Performance
Reaction to fire		Class E
Resistance to flow		≤3 mm
Loss of volume		≤10 %
Secant tensile modulus at -30°C		≤0,9 MPa
Tensile properties at maintained extension at -30°C		Pass
Adhesion/cohesion properties after exposure to heat water and artificial light		Pass
Elastic recovery		≥60 %
Durability		Pass
Release of dangerous substances		Vedi SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Etienne Guichard (legal representative)

At Corbas, on 30/09/2019



kerakoll.com



DECLARATION OF PERFORMANCE No. 0394

1. Unique identification code of the product-type: Fugabella Eco Silicone

2. Intended use/es: Sealant for non-structural use: sanitary joints.

3. Manufacturer: Kerakoli France 25, avenue de l'Industrie 69960 Corbas - France

4. System/s of AVCP:

System 3 and System 3 for reaction to fire

5. Harmonised standard: EN 15651-3:2012

Notified body/ies: SKZ - TeConA GmbH, No. 1213

6. Declared performance/s:

EN15651-3 S (Class XS1)

Pretreatment: Method A

Substrate: glass; without primer

aluminium; without primer

Essential characteristics	Performance
Reaction to fire	Class E
Resistance to flow	≤ 3 mm
Loss of volume	≤ 20%
Tensile properties at maintained extension after immersion in water	Pass
Microbiological growth	1
Durability	Pass
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Etienne Guichard (legal representative)

At Corbas, on 30/09/2019





DECLARATION OF PERFORMANCE No. 0394

- 1. Unique identification code of the product-type: Fugabella Eco Silicone
- 2. Intended use/es: Sealant for movement joints in floors for interior and exterior application, for non-structural use; included cold climates.
- 3. Manufacturer: Kerakoll France 25, avenue de l'Industrie 69960 Corbas France
- 4. System/s of AVCP:

System 3 and System 4 for reaction to fire

5. Harmonised standard: EN 15651-4:2012

Notified body/ies: SKZ - TeConA GmbH, No. 1213

6. Declared performance/s:

EN15651-4 PW-EXT-INT-CC (Classe 12,5 E)

Pretreatment: Method A

Substrate: mortar M1 with primer

Essential characteristics	Performance
Reaction to fire	Class E
Loss of volume	≤ 15%
Tensile properties at maintained extension	Pass
Adhesion / cohesion properties at maintained extension after water immersion	Pass
Adhesion / cohesion properties at maintained extension after salt water immersion	Pass
Tensile properties at maintained extension for non-structural sealants used in joints in cold climate areas (-30°C)	Pass
Tear resistance	Pass
Durability	Pass
Release of dangerous substances	Vedi SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Etienne Guichard (General Manager)

At Corbas. on 30/09/2019

kerakoll.com

KERAKOLL FRANCE - au capital de € 6.500.000,00